#### SMARTSEAL - MOSS CLEAR PRO

Page: 1

Compilation date: 18/02/2021

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

### Product name: SMARTSEAL - MOSS CLEAR PRO

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of substance / mixture: A COMPLEX MIXTURE OF CLEANING

CHEMICALS

### **1.3. Details of the supplier of the safety data sheet**

# Company name: SMARTSEAL UNIT 3, 65-67 CUTLERS ROAD SOUTH WOODHAM FERRERS CHELMSFORD ESSEX CM35WA

United Kingdom

Tel: 01268 722500

Email: contactus@smartseal.co.uk

### 1.4. Emergency telephone number

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Most important adverse effects: Causes severe skin burns and eye damage.

## 2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Hazard pictograms: GHS05: Corrosion



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

## SMARTSEAL - MOSS CLEAR PRO

Rinse skin with water .

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

## 2.3. Other hazards

## **PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

## 3.2. Mixtures

### Hazardous ingredients:

#### QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C8-18-ALKYLDIMETHYL, CHLORIDES

EINECS	CAS	PBT / WEL	CLP Classification	Percent
264-151-6	63449-41-2	-	Acute Tox. 4: H312; Acute Tox. 4: H302;	1-10%
			Skin Corr. 1B: H314; Aquatic Acute 1:	
			H400	

### Section 4: First aid measures

4.1. Description of first aid measures		
Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin.	
	Drench the affected skin with running water for 10 minutes or longer if substance is still	
	on skin. Transfer to hospital if there are burns or symptoms of poisoning.	
Eye contact:	Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist	
	examination.	
Ingestion:	Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10	
	minutes. If unconscious, check for breathing and apply artificial respiration if necessary.	
	If unconscious and breathing is OK, place in the recovery position. Transfer to hospital	
	as soon as possible.	
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. If	
	unconscious and breathing is OK, place in the recovery position. If conscious, ensure	
	the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and	
	provide oxygen if available. Transfer to hospital as soon as possible.	
4.2. Most important symptoms	and effects, both acute and delayed	
Skin contact:	Blistering may occur. Progressive ulceration will occur if treatment is not immediate.	
Eye contact:	Corneal burns may occur. May cause permanent damage.	
Ingestion:	Corrosive burns may appear around the lips. Blood may be vomited. There may be	
	bleeding from the mouth or nose.	
Inhalation:	There may be shortness of breath with a burning sensation in the throat. Exposure may	
	cause coughing or wheezing.	
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.	

Page: 2

### SMARTSEAL - MOSS CLEAR PRO

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

#### SMARTSEAL - MOSS CLEAR PRO

Page: 4

### 7.3. Specific end use(s)

Specific end use(s): No data available.

### Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

Workplace exposure limits: No data available.

## **DNEL/PNEC** Values

DNEL / PNEC No data available.

8.2. Exposure controls

 Engineering measures:
 Ensure there is sufficient ventilation of the area.

 Respiratory protection:
 Self-contained breathing apparatus must be available in case of emergency.

 Hand protection:
 Impermeable gloves.

 Eye protection:
 Tightly fitting safety goggles. Ensure eye bath is to hand.

 Skin protection:
 Impermeable protective clothing.

#### Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

State:	Liquid	
Colour:	Dark green	
Odour:	Aromatic	
Evaporation rate:	No data available.	
Oxidising:	No data available.	
Solubility in water:	Highly soluble	
Viscosity:	Non-viscous	
Boiling point/range°C:	No data available. Melting point/range°C:	No data available.
Flammability limits %: lower:	Not applicable. upper:	Not applicable.
Flash point°C:	Not applicable. Part.coeff. n-octanol/water:	Not applicable.
Autoflammability°C:	Not applicable. Vapour pressure:	No data available.
pH:	7	

9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

#### SMARTSEAL - MOSS CLEAR PRO

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

Conditions to avoid: Heat.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

11.1. Information on toxicological effects

#### Hazardous ingredients:

### QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C8-18-ALKYLDIMETHYL, CHLORIDES

IVN	MUS	LD50	16	mg/kg
ORL	MUS	LD50	150	mg/kg

#### **Relevant hazards for product:**

Hazard	Route Basis	
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

## Excluded hazards for substance:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	-	Based on available data the classification criteria are not met
Acute toxicity (ac. tox. 3)	-	Based on available data the classification criteria are not met
Acute toxicity (ac. tox. 2)	-	Based on available data the classification criteria are not met
Acute toxicity (ac. tox. 1)	-	Based on available data the classification criteria are not met

## Symptoms / routes of exposure

Skin contact:	Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
Eye contact:	Corneal burns may occur. May cause permanent damage.
Ingestion:	Corrosive burns may appear around the lips. Blood may be vomited. There may be
	bleeding from the mouth or nose.
Inhalation:	There may be shortness of breath with a burning sensation in the throat. Exposure may
	cause coughing or wheezing.

### SMARTSEAL - MOSS CLEAR PRO

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

#### Section 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

### Section 14: Transport information

14.1. UN number

UN number: UN1760

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

### SMARTSEAL - MOSS CLEAR PRO

### 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 2

## Section 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

Other information		
Other information:	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation	
	(EU) 2015/830	
	* indicates text in the SDS which has changed since the last revision.	
Phrases used in s.2 and s.3:	H302: Harmful if swallowed.	
	H312: Harmful in contact with skin.	
	H314: Causes severe skin burns and eye damage.	
	H400: Very toxic to aquatic life.	
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive	
	and shall be used only as a guide. This company shall not be held liable for any	
	damage resulting from handling or from contact with the above product.	